

KAM-U-BUL2MP

Udendørs 2MP IP Bullet kamera IR, med Wide Dynamic Range. 2.7 - 12mm linse. PoE eller 12VDC

FEATURES

- 1/2.8" scan CMOS
- 2.7 - 12mm motor linse
- 2MP (1920×1080)
- IR (nattesyn) op til 30 meter
- IP67 udendørs. Med skjold
- Synsvinkel: 105 - 32 grader
- H.265, H.264, MJPEG
- POE eller 12VDC
- driftstemperatur: -40°C ~ 60°C
- Dimensioner: 264.5×82.7×80.3 mm
- Vægt: 830 g



SPECIFICATIONS

Billede	:	1/2.8" Progressive Scan CMOS
Certifications	:	CE / FCC
Dimensioner	:	264.5×82.7×80.3mm
Driftstemperatur	:	-40°C ~ 60°C
Ethernet	:	1 Ethernet (10/100 Base-T) RJ-45 Connector
Forsyning	:	POE, 12VDC
Funktioner	:	True WDR-12dB
Kamera	:	IR afstand op til 30 meter
Linse	:	Motor linse
Materiale	:	Metal
Opløsning	:	Maks. 1080P(1920×1080)
OS SUPPORT	:	IOS, Android. virker på internet explorer, chrome, firefox

KAM-U-BUL2MP

SPECIFICATIONS

Protokol	:	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP
Strømforbrug	:	3W (IR LED OFF), 8W (IR LED ON)
Video	:	H.265, H.264, MJPEG
Vægt	:	830g