

MON10.1-TFT-T

10.1" LCD Touch Screen Alu Front, Projected
Capacitive Touch 1280x800 16:10, IP66 Front, DC
9 ~ 36V

FEATURES

- 10.1" TFT 1280x800 (16:10)
- Front panel IP66 Standard / IP69K Option
- Aluminum cabinet
- VGA, DVI, HDMI and DP Input
- Supply voltage: DC 9 ~ 36V
- Contrast : 800:1
- Brightness: 350 Nits Standard / 1000 Nits Option
- Touch Via USB: Projected Capacitive Standard / Resistive Option / No Touch Option
- Touch Via RS232: Option
- VESA 100 and Panel Mount
- Dimensions: 285 x 189 x 48.9mm
- Weight: 1.9 kg
- Operating temperature: 0 ~ +50°C Standard / -20 ~ +60°C Option



SPECIFICATIONS

| | | |
|---------------|---|---|
| Andet | : | 15G peak acceleration (11 msec. duration) / Operation |
| Dimensioner | : | 285 x 189 x 48.9mm |
| Drivere | : | eGalaxTouch |
| Forsyning | : | DC 9 ~ 36V |
| Indgang | : | USB |
| IP-Tæthed | : | IP66 front |
| Kabinet | : | Aluminum die-casting chassis |
| Montering | : | Panel and VESA |
| Opløsning | : | 1280x800 16:10 |
| OS SUPPORT | : | Windows XP, Vista, 7, 8, CE, Mac og Linux |
| Touch | : | USB, PCAP |
| VESA standard | : | 100 x 100mm |



DANBIT A/S - Dansk Binær Teknik
Værkstedsvvej 39 Køge, 4600 Danmark



+45 56 66 20
20




salg@danbit.dk




DANBIT

MON10.1-TFT-T

SPECIFICATIONS

 DANBIT A/S - Dansk Binær Teknik
Værkstedsvvej 39 Køge , 4600 Danmark

 +45 56 66 20
20

 salg@danbit.dk

All prices are excl. VAT and delivery
 Reservations are made for obsolete items and errors in data