

## SDI4MULTI-G

4 ports splitter SDI, SD-SDI, HD-SDI, 3G-SDI. 1 x BNC inputs and 4 x BNC output. Same output image. 5VDC

## FEATURES

4 Port SDI multimedia splitter  
same image on the four monitors up to 100 meters  
Compatible with SD-SDI, HD-SDI and 3D SDI to 5 x BNC female  
1 x BNC - SDI input to 4 x BNC - SDI output  
SD 525i and 625i  
HD 720p 24/25/30/50/60Hz, HD 1080i 50/60Hz  
HD 1080p 24/25/30/50/60Hz  
Supply voltage: 5VDC PSU included  
Dimensions: 130 x 77 x 24 mm



## SPECIFICATIONS

Afstand	:	p til 100 m kabellængde v. 3G-SDI (2,97 Gb/s) på ind- og udgangene
Andet	:	Power consumption: 250mA (DC 5V)
Dimensioner	:	130 x 77 x 24mm (L x W x H)
Driftstemperatur	:	0~+60 °
Kompatibilitet	:	SD-SDI, HD-SDI og 3G-SDI
Opløsning	:	Op til 1920 x 1080i/p ved 60 Hz
Output	:	SDI signal output amplitude: 800mVp-p
Strømforsyning	:	Forsynes af medfølgende 5 VDC 1 A netadapter
Udgange	:	4 x BNC hun, indgange: 1 x BNC hun



DANBIT A/S - Dansk Binær Teknik  
Værkstedsvvej 39 Køge , 4600 Danmark



+45 56 66 20  
20



salg@danbit.dk