

RS232 serial port amplifier, all baud rate up to 120kbps.

### FEATURES

- Extend serial cable up to 1600 meters, transiently protected
- RS232 / V.24
- Transparent data: synchronous and asynchronous
- All HW and software handshakes
- DB25 male and DB25 female
- With screw terminal connection of serial I / O
- With RJ45 connection of serial from special cable
- DC9V / 2A power supply included



DANBIT A/S - Dansk Binær Teknik  
Værkstedsvvej 39 Køge , 4600 Danmark



+45 56 66 20 20



salg@danbit.dk

## SPECIFICATIONS

|            |   |  |
|------------|---|--|
| Forsyning  | : | DCE DB25 hunstik DTE DB25 hanstik  |
| Hastighed  | : | Op til 115,2 Kbit/s  |
| Kabel      | : | Kabellængde fra pc til indgang kan være op til 1600 meter  |
| Signaler   | : | TxD, RxD, RTS, CTS, DSR, DCD, DTR og GND ført ud til 8 pin skrueterminal og et RJ45 stik for hver port |
| Standarder | : | RS232 (alle 25 ledere på RS232/V24)  |
| Type       | : | Booster til seriel port  |



DANBIT A/S - Dansk Binær Teknik  
Værkstedsvvej 39 Køge , 4600 Danmark



+45 56 66 20 20



salg@danbit.dk