

UHF 865MHz RFID reader, outdoor, with 2 - 5 m reading distance, for passive UHF TAGs, COM port, SDK

## FEATURES

- For passive UHF tags 865MHz
- Supports ISO18000-6B, ISO18000-6C
- RF power: 0.1 - 1 Watt
- TAG reading is controlled via software commands
- Interface: RS232, RS485 and Wiegand 26/32
- Circular polarized antenna
- RS-232, RS-485, Wiegand 26Bits/32Bits
- 5V DC power supply / 2 Watt
- Dimensions: 220 x 220 x 50 mm
- Weight: 1.5 kg
- IP65



## SPECIFICATIONS

Dimensioner	:	215 ´ 215 ´ 60 mm
Driftstemperatur	:	-35 til +65 °C
Forsyning	:	12 VDC, 2 A. 230VAC adapter medfølger
Frekvens	:	865-868 MHz
Hastighed	:	Op til 30 km/t på tværs af læsefelt
Interface	:	RS232, RS485 og Wiegand 26/34
Max læseafstand	:	Typisk 2 - 4 m, mere under ideelle forhold
Miljø	:	IP54 tæthed. Egnet til udendørs brug
Montering	:	Rørbeslag, justerbart horisontalt og vertikalt
Vertikal spredning	:	70°