

2500VA UPS, uninterruptible power supply - line interactive, incl. batteries. with RS232

## FEATURES

- Assembled before delivery! Usually in stock
- 2500VA UPS
- Modified sine wave to 5 hours of recharging time
- Alarm v. Low battery and overvoltage
- Connector: 4 x IEC ed and 1 x IEC engrave.
- 1 x RS232 / DB9 female connector
- Operating temperature: 0-40 °
- Supports automatic shutdown via software
- download included. 4 x 12V / 12 Ah battery



## SPECIFICATIONS

Alarm	:	Bip hvert 3. sekund hvis batteri er aktivt, bip hvert sekund hvis batteriniveau er lavt og kontinuerligt bip ved overspænding
Batteri	:	4 x 12 V 12 Ah
Beskyttelse	:	Mod over- og underspændinger, overbelastning og kortslutning
Dimensioner	:	197 x 143 x 408 mm
Genopladningstid	:	(90 %) 5 timer
Interface	:	RS232 serielport, DB9 hunstik. Ved backup tilstand kan der sendes signal via denne port
Software	:	Der medfølger software, der giver avanceret information, såsom ladestatus, ind- og udgangsspændinger, e-mail advarsel, skemalagt test af UPS og meget mere.
Spændingsform	:	Modificeret sinuskurve
Stik	:	4 x IEC stik til udgang og 1 x IEC stik til indgang (standard pc spændingsforsyningsstik)
Støj	:	Under 40 dB (ved 1 meter)
Weight	:	UPS: 15 kg, batteripakke: 20 kg

