

REL8OPT8PCI

Adlink PCI-7250. 8 kanalers relæ output, 8 kanalers isolerede digitale input, PCI

FEATURES

- Antal af ind- og udgange kan udvides til 32
- Supports a 32-bit 5 V PCI bus
- 8-CH relay outputs
- 8-CH isolated DI
- On-board LED indicators for relay status
- On-board relay driving circuits
- Relay output stats read back
- On-board low-pass filtering for DI
- Extendable up to 32-CH relay outputs



SPECIFICATIONS

Dimensioner	:	107 x 162 mm
Indgang	:	8 optoisolerede (PC814). Begge ledere er ført ud for hver indgang Indgangsniveau: Ikke polariseret Logisk 0: 0 - 1,5 VDC Logisk 1: 5 - 24 VDC
Isolation	:	2.500 VDC
Software	:	Drivere til DOS, Windows 2000, XP, Win7 og Win8 Linux og Labview medfølger
Stik	:	DB37 hun
Udgange	:	8 relæer, 4 slutte (form A), 4 skifte (form C) Belastning: 120 VAC/DC 0,5 A / 24 VDC 1 A Skiftetid: Typisk 8 ms



DANBIT A/S - Dansk Binær Teknik
Værkstedsvvej 39 Køge , 4600 Danmark



+45 56 66 20
20



salg@danbit.dk