

ESW10U-FM

10-ports växel 8 x 10 / 100Mbit RJ45 + 2 x
fiberport SC Gigabit Multi Mode, Unhaneaged, 12-
48VDC

FEATURES

- 8 x 10 / 100Mb RJ-45-portar inte hanterad switch
- 2 x Gigabit SC uplink-portar
- Broadcast storm skydd
- IEEE802.3x Full duplex, flödesreglering
- Redundant dual DC kraftingångar
- Robust hölje
- Reläutgång Aktiverar relä
- Stöder upp till 8K MAC-adresser



SPECIFICATIONS

Övrig	:	Broadcast storm filter, Store-and-forward, Relæudgang der trækkes ved fejl
Forsyning	:	2 redundante forsyningsindgange, 12/24/48 VDC. Leveres uden strømforsyning, maks 14,5 W
Hastighed	:	8 x 10/100Mbit
Indikatorer og kontakter	:	On/off, link og aktivitet
IP-Tæthed	:	IP50
Miljø	:	-40 °C ~ 80 °C ved luftfugtighed på 5 til 95 %
Montering	:	DIN-skinne
Porte	:	8 x RJ-45, 2 x SC
Standarder	:	EN50155, EN50121-4, MIL-STD-810F, UL60950-1
Fibermode	:	multimode



DANBIT A/S - Dansk Binær Teknik
Værkstedsvvej 39 Køge , 4600 Danmark



+45 56 66 20
20



salg@danbit.dk