

ETH1SER-K

1 port seriell port server RS232 / 422/485. Serie
Device Server Korenix JETPORT 5601

FEATURES

- Extern COM-port över nätverksanslutning
seriell port via db9 hanee
- 2 x RJ45 Nätverksanslutningar



DANBIT A/S - Dansk Binær Teknik
Værkstedsvvej 39 Køge , 4600 Danmark



+45 56 66 20
20



salg@danbit.dk

SPECIFICATIONS

Administration	:	Indstilles via netværk over krypteret http (https) vha. enten SSH konsol eller Jetport Commander Windowsprogram
Övrig	:	Seriell porten kan sende data til 5 modtagere simultant. Leveres inkl. 100 ~ 240 VAC adapter, program CD og manualer
Dimensioner	:	29,6 x 88 x 114,8 (H x B x D)
Driftstemperatur	:	-20 ~ 70°C
Isolation	:	1,5 kV galvanisk isolation
Kompatibilitet	:	COM drivere til WIN10/8/7 (32/64 bit), 2000/ XP/2003 og Vista
Montering	:	DIN skinne monteringsdele og vægbeslag
Netværk	:	2 x 10/100 Mbit Ethernet redundant netværksport, auto fallback less than 200 ms
Porte	:	En port, der kan bruges som RS232, RS422 eller RS485. Hastigheder fra 110 til 460 Kbit/s, Databit:5/6/7/8, Stopbit:1/1,5/2. Paritet: Lige/Ulige/Ingen
Protokol	:	TCP, UDP, Telnet, DHCP, ICMP, https, SSH, BootP, ARP, DNS, SNMP
Stik	:	Seriell port: DB9 hanstik. Ethernet: 2 x RJ45 hunstik
Strømforsyning	:	Redundant spændingsforsyning: 9 ~ 30 VDC via 5.5 mm jack (hun) strømstik. 12 ~ 48 VDC via skrueterminaler

